



Submittal Data Sheet	GSSHAX7487 / GSSHAX7488
208-230V 9000 BTU Indoor/Outdoor Mini Split	



Efficiency				
	SEER2	EER2	HSPF2	COP2
Non-Ducted	19	10	8.5	3.41

Performance	
Cooling (Btu/hr)	
Rated	9,000
Operating Range	60.8 – 87.8°F
Ambient Temperature:	Indoor: >=62.6°F Outdoor: 5°F - 122°F
Heating (Btu/hr)	
Rated	10,000
Operating Range	60.8 – 87.8°F
Ambient Temperature:	Indoor: <= 86°F Outdoor: -4°F - 86°F

Complete warranty details available from your local dealer or at www.lloydnorthamerica.com. To receive the 5-Year Parts/7-Year compressor Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. If product is installed in a commercial application, limited warranty period is 5 years.

Electrical	
Power Supply	208-230/60/1
Maximum Fuse Size	15A
Rated Input Consumption (C)	810W
Rated Input Consumption (H)	970W
Rated Current (C)	3.6A
Rated Current (H)	4.4A

Specifications				
Compressor	Rotary			
Refrigerant	R-410A			
Factory Charge (Lbs)	1.76			
Refrigerant Oil	PVE (FVC50K)			
Airflow Rate (cfm)	Indoor		Outdoor	
	H	353	H	1110
Sound Pressure Level (dBA)	50			
Outdoor Dimensions (H x W x D) (in)	28.14x11.42x19.61			
Outdoor Weight (Lbs)	54.1			
Indoor Dimensions (H x W x D) (in)	31.92x11.49x8.07			
Indoor Weight (Lbs)	19.8			

Piping	
Liquid (in)	1/4
Gas (in)	3/8
Max. System Piping Length (ft)	50
Max. Interunit Piping Length (ft)	82
Max. Height Difference – IDU to ODU (ft)	33
Chargeless (ft)	98.5

Lloyd North America

(Lloyd's products are subject to continuous improvements. Lloyd reserves the right to modify product design, specifications, and information in this data sheet without notice and without incurring any obligations)

Submittal Revision Date: March 2023