



<b>Submittal Data Sheet</b>	GSSHAX7493 / GSSHAX7494
208-230V 18,000 BTU Indoor/Outdoor Mini Split	



Efficiency				
	SEER2	EER2	HSPF2	COP2
<b>Non-Ducted</b>	19	9.4	8.5	3.21

Performance	
<b>Cooling (Btu/hr)</b>	
<b>Rated</b>	18,000
<b>Operating Range</b>	60.8 – 87.8°F
<b>Ambient Temperature:</b>	Indoor: >=62.6°F Outdoor: 5°F - 122°F
<b>Heating (Btu/hr)</b>	
<b>Rated</b>	19,600
<b>Operating Range</b>	60.8 – 87.8°F
<b>Ambient Temperature:</b>	Indoor: <= 86°F Outdoor: -4°F - 86°F

Complete warranty details available from your local dealer or at [www.lloydnorthamerica.com](http://www.lloydnorthamerica.com). To receive the 5-Year Parts/7-Year compressor Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. If product is installed in a commercial application, limited warranty period is 5 years.

Electrical	
Power Supply	208-230/60/1
Maximum Fuse Size	20A
Rated Input Consumption (C)	1800W
Rated Input Consumption (H)	1850W
Rated Current (C)	8A
Rated Current (H)	8.3A

Specifications				
Compressor	Rotary			
Refrigerant	R-410A			
Factory Charge (Lbs)	2.36			
Refrigerant Oil	PVE (FVC50K)			
Airflow Rate (cfm)	<b>Indoor</b>		<b>Outdoor</b>	
	H	606	H	1520
Sound Pressure Level (dBA)	52			
Outdoor Dimensions (H x W x D) (in)	30.70x13.74x23.81			
Outdoor Weight (Lbs)	73.8			
Indoor Dimensions (H x W x D) (in)	39.76x12.40x8.66			
Indoor Weight (Lbs)	28.7			

Piping	
Liquid (in)	1/4
Gas (in)	3/8
Max. System Piping Length (ft)	65
Max. Interunit Piping Length (ft)	82
Max. Height Difference – IDU to ODU (ft)	49
Chargeless (ft)	98.5